

# High Speed Door **Systems**



PRODUCT LINE

RAPIDFLEX® FABRIC DOORS  
RAPIDFLEX® RUBBER DOORS  
RAPIDFREEZE® FABRIC DOORS  
RAPIDSHIELD® METAL DOORS  
RAPIDVIEW® FULL-VIEW METAL DOORS

MODELS

990/991/992/993/994

995/995LH

997

998

999



**INDUSTRY EXPERTS,  
DELIVERING TOTAL SOLUTIONS**



**High Performance Doors That Are as Fast, Reliable and Versatile as your Business**

The RapidFlex®, RapidFreeze®, RapidShield® and RapidView® series of high performance doors are engineered to allow maximum productivity with fast-acting curtains, high-cycle performance and resistance to damage from accidental collisions. With robust safety features and a pressure resistant design, these high speed doors will keep your facility running securely, efficiently and environmentally controlled.

**General Features and Benefits**

**Springless, High Cycle Design**

- Minimizes down-time, ideal for high cycle applications

**Fast-acting**

- Fully opens in 4 seconds or less\*

**Breakaway Bottom**

- Designed to break away from the side guides
- Simple reset and self repair after a break-away event
- Impact detection

**Airtight Guides** (Model 991)

- Tight sealing guides resist air pressure
- Help control environments; minimize debris

**Direct Gear Drive System**

- Eliminates the wear and tear associated with conventional chain and sprocket systems
- Advanced gearbox design features door stop safety device

**Robust Safety Features**

- Dual infrared sensors
- Wireless bottom reversing edge
- Flexible bottom edge (Model 990)
- Built-in door stop device
- Safety light curtain minimizes contact with objects in the doorway
  - Integrated (Standard for Models 998 & 999)
  - Externally mounted (optional for Models 990-995)

**Independently Tested**

- Air infiltration (Model 991)
- Wind load

**Hood Standard** (Models 990, 991, 992, 993, 994, 995)

**Padlockable Disconnect at Controller**

**Plug and Play Wiring**

\*Depending on opening height and door models

Cover image: Model 994, Blue

Image above: Model 995, Black




**Standard Product Features**



**Patented Curtain Lock**

Enables doors to be repaired quickly and in the field, unlike zippered doors. (Models 990 and 991).



**Patented Roller Wind Strut**

Heavy-duty strut with roller wind lock enhances curtain strength. (Models 993 and 994).



**Wireless Reversing Edge**

Designed to reverse with minimum contact load.



**Obstruction Detection**

Features two in-plane infrared sensors, minimizing contact with objects in the doorway. (Standard on Models 990-997. Optional on Models 998-999).




**Traveling Wind Bar**

Provides added structural support and enhanced operation in demanding operations (Model 995).



**New Advanced Control Panel\***

Features circular LED light ring with flexible activation profiles, automatic adjustment of operator frequency to prevent a fault or stopping the door.




**Light Curtain Obstruction Detection**

6' integrated light curtain (Models 998, 999). Front or rear mounted light curtain available in 3' or 6' (Models 990 through 995).



**Direct Drive Motor**

Advanced gearbox features door stop safety device is design to reduce maintenance costs and increase durability.



**Patented Helical Design Head Plate**

Prevents metal curtain contact and provides smooth operation. (Models 998 and 999).



**Flexible Bottom Bar with Detachable Bottom Seal**

Allows for easy replacement and troubleshooting. (Model 990).

\* Subject to model selection. Late availability.

**Options**

**Signaling Device Options**

Red/green LED traffic light, horn/strobe combination, rotating warning light.

**Actuation Options**

Push button, key switch, pull switch, loop detector, motion detector, treadle switch, radio control. Wireless options: pull switch, 1 or 3-button push button, palm button.

**Programmable LED Lighting System**

3" tall light bar with red, yellow, green lights. Available in 1, 2, 3 or 4 strip options

**Cooler Application**

Air curtain options available included heated or non-heated, steel or stainless steel and various voltage offerings (Model 991).

**Sensor Options**

Designed to provide varying levels of functionality and performance.



BEA Widescan



BEA Falcon



BEA IS40/XL



Miller Edge M Wave




Optex OAM Explorer

# HIGH SPEED FABRIC DOORS

Flexible Bottom  
Fabric Door  
**RAPIDFLEX® 990**












Fabric Door  
**RAPIDFLEX® 991**



Strutted  
Fabric Door  
**RAPIDFLEX® 992**



## Features

Application	Manufacturing; Distribution; Food/Beverage; Pharmaceutical	Manufacturing; Distribution; Food/Beverage; Cooler; Cold Storage; Pharmaceutical	Manufacturing; Distribution; Food/Beverage; Cold Storage
Location of Opening (Mount)	<b>Interior</b>	<b>Interior</b>	<b>Interior/Exterior (Mount Inside/Outside)</b>
Maximum Width*	12'	14'	16'
Maximum Height*	12'	14'	15'
Opening Speed	Up to 70"/sec	Up to 70"/sec	Up to 65"/sec
Closing Speed	Up to 40"/sec	Up to 40"/sec	Up to 40"/sec
Certified Air Tightness <sup>1</sup>	N/A	< 0.236 cfm/sq ft	N/A
Curtain Lock	Yes	Yes	N/A
Break Away Self Reset	Yes	Yes	Yes
Wind Load <sup>2</sup>	Up to 3.0 psf	Up to 7.5 psf	Up to 4.0 psf
Wind Strut	N/A	N/A	1" strut standard
Traveling Wind Bar	N/A	N/A	N/A
Curtain Material	2 layers of light PVC-coated polyester with 1 layer of polyester weave	2 layers of PVC-coated polyester with 1 layer of polyester weave	Interior: 2 layers of PVC-coated polyester with 1 layer of polyester weave; Exterior/Interior: 3 layers of PVC-coated polyester with 2 layers of polyester weave
Vision	Optional 20" high vision panels spaced evenly across width of door	Optional 20" high vision panels spaced evenly across width of door	Optional 20" high vision panels spaced evenly across width of door
Operation	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device
Control Panel	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder Built-in padlockable fused disconnect	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder Built-in padlockable fused disconnect	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder Built-in padlockable fused disconnect
Obstruction Safety Detection	Infrared sensors mounted in-plane to the door curtain at 18" and 50" - 54" from floor; Optional front or rear mounted light curtain.	Infrared sensors mounted in-plane to the door curtain at 18" and 50" - 54" from floor; Optional front or rear mounted light curtain.	Infrared sensors mounted in-plane to the door curtain at 18" and 50" - 54" from floor; Optional front or rear mounted light curtain.
Reversing Safety Edge	Wireless reversing edge; Flexible bottom bar with detachable bottom seal	Wireless reversing edge	Wireless reversing edge
Available Supply Voltages <sup>3</sup>	120V AC 1PH, 208V AC 1PH <sup>1</sup> , 220V AC 1PH, 208V AC 3PH <sup>1</sup> , 230V AC 3PH, 460V AC 3PH, 575V 3PH <sup>1</sup> (requires stand-alone mounted transformer)	120V AC 1PH, 208V AC 1PH <sup>1</sup> , 220V AC 1PH, 208V AC 3PH <sup>1</sup> , 230V AC 3PH, 460V AC 3PH, 575V 3PH <sup>1</sup> (requires stand-alone mounted transformer)	120V AC 1PH, 208V AC 1PH <sup>1</sup> , 220V AC 1PH, 208V AC 3PH <sup>1</sup> , 230V AC 3PH, 460V AC 3PH, 575V 3PH <sup>1</sup> (requires stand-alone mounted transformer)
Hinged Guides	Provides easy access for maintenance	Provides easy access for maintenance	Provides easy access for maintenance
Warranty	5-year limited on drive motor and gearbox; 1-year limited on all other components	5-year limited	5-year limited
Curtain Color Options Actual colors may vary due to fluctuation in the printing process. Always request a color sample from your Overhead Door™ Distributor for accurate color matching.	 Red  Blue  White	 Gray  Black (991/992 only)  Orange (991/992 only)	 Yellow (991/992 only)  FDA Royal Blue (991/992 only)  FDA White (991/992 only)

## Notes

<sup>2</sup> Wind load is the ultimate pressure tested at door width of 12'.

<sup>1</sup> Air tightness is independently tested to ASTM E283 test standard.  
Wind load is the ultimate pressure tested at door width of 10'.

<sup>2</sup> Wind load is the ultimate pressure tested at door width of 16'.

\* Height and width of door may affect opening speed. Please consult factory for specifics.



Strutted Heavy-Duty  
Fabric Door

**RAPIDFLEX® 993**



Manufacturing; Distribution;  
Auto/Transit; Parking; Food/Beverage

**Exterior (Mount Inside/Outside)**

20'

20'

Up to 65"/sec

Up to 40"/sec

N/A

N/A

Yes

Up to 19.5 psf

Metal struts with roller wind lock

N/A

3 layers of PVC-coated polyester with  
2 layers of polyester weave

Optional 20" vision panels spaced  
evenly across width of door

Direct drive motor and gearbox system  
with field changeable universal handing  
and door stop safety device

Variable frequency drive  
NEMA 4X cULus listed;  
Onboard self diagnostic and service reminder;  
Built-in padlockable fused disconnect

Infrared sensors mounted in-plane to the door  
curtain at 18" and 50" - 54" from floor; Optional front  
or rear mounted light curtain.

Wireless reversing edge

120V AC 1PH, 208V AC 1PH<sup>†</sup>, 220V AC 1PH,  
208V AC 3PH<sup>†</sup>, 230V AC 3PH, 460V AC 3PH, 575V 3PH<sup>†</sup>  
(<sup>†</sup>requires stand-alone mounted transformer)

Provides easy access for maintenance

5-Year Limited



Red

Blue

Orange

Gray

Above colors also available for Model 992 with  
optional exterior/interior curtain material.

## RAPIDFLEX®/RAPIDFREEZE® FABRIC DOORS

MODELS 990/991/992/993

Ideal for separating controlled environment spaces such as food and beverage facilities, high traffic zones, storage rooms, freezer and cooler applications and manufacturing areas to prevent cross-contamination.

- Dual wind lock allows for quiet and smooth operation on Models 990 and 991
- Flexible bottom bar with detachable seal for easy replacement and troubleshooting on Model 990
- Heavy-duty strut with roller wind lock on Model 993
- Air curtain options available for Model 991



<sup>2</sup> Wind load is the ultimate pressure tested at door width of 20'.

Model 994, Gray, windows

# HIGH SPEED FABRIC, RUBBER & METAL DOORS

Struttred Maximum Strength  
Fabric Door  
**RAPIDFLEX® 994**



Extreme  
Rubber Door  
**RAPIDFLEX® 995**



Low Headroom  
Rubber Door  
**RAPIDFLEX® 995LH**



Extreme  
Fabric Door  
**RAPIDFREEZE® 997**



Features

Application	Manufacturing; Distribution; Mining; Auto/Transit; Parking	Manufacturing; Distribution; Mining; Auto/Transit; Parking	Manufacturing; Distribution; Mining; Auto/Transit; Parking	Cold storage; Food/Beverage; Distribution
Location of Opening (Mount)	<b>Exterior</b> (Mount Inside/Outside)	<b>Exterior</b> (Mount Inside/Outside)	<b>Exterior</b> (Mount Inside/Outside)	<b>Interior</b>
Maximum Width*	24'	30'	22'	12'
Maximum Height*	18' at 24' wide or 20' at 23' wide	30'	10'	18'
Opening Speed	Up to 55"/sec	Up to 50"/sec	Up to 30"/sec	Up to 80"/sec
Closing Speed	Up to 40"/sec	Up to 40"/sec	Up to 20"/sec	Up to 40"/sec
Certified Air Tightness <sup>1</sup>	N/A	N/A	N/A	N/A
Curtain Lock	N/A	Yes	Yes	N/A
Break Away Self Reset	Yes	Yes	No <sup>1</sup>	Yes
Wind Load <sup>2</sup>	Up to 22.0 psf	Up to 27.0 psf	Up to 27.0 psf	Up to 2.0 psf
Wind Strut	4" articulating roller wind strut	N/A	N/A	N/A
Traveling Wind Bar	N/A	Optional	N/A	N/A
Curtain Material	3 layers of PVC-coated polyester with 2 layers of polyester weave	5 layers of NBR Rubber with 4 layers of polyester weave	5 layers of NBR Rubber with 4 layers of polyester weave	2 layers of PVC-coated polyester with 1 layer of polyester weave and conductive plus radiant insulation
Vision	Optional 20" high vision panels spaced evenly across width of door	Optional 20" high vision panels spaced evenly across width of door	Optional 20" high vision panels spaced evenly across width of door	N/A
Operation	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device
Control Panel	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder; Built-in padlockable fused disconnect	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder; Built-in padlockable fused disconnect	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder; Built-in padlockable fused disconnect	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder; Built-in padlockable fused disconnect; Includes power for guide heater and air curtain
Obstruction Safety Detection	Infrared sensors mounted in-plane to the door curtain at 18" and 50"- 54" from floor; Optional front or rear mounted light curtain.	Infrared sensors mounted in-plane to the door curtain at 4.5" and 50"- 54" from floor; Optional front or rear mounted light curtain.	Infrared sensors mounted in-plane to the door curtain at 4.5" and 50"- 54" from floor; Optional front or rear mounted light curtain.	Infrared sensors mounted in-plane to the door curtain at 16" and 50"- 54" from floor
Reversing Safety Edge	Wireless reversing edge	Wireless reversing edge	Wireless reversing edge	Wireless reversing edge
Available Supply Voltages <sup>3</sup>	208V AC 3PH <sup>†</sup> , 230V AC 3PH, 460V AC 3PH, 575V AC 3PH <sup>†</sup> (*requires stand-alone mounted transformer)	208V AC 3PH <sup>†</sup> , 230V AC 3PH, 460V AC 3PH, 575V AC 3PH <sup>†</sup> (*requires stand-alone mounted transformer)	208V AC 3PH <sup>†</sup> , 230V AC 3PH, 460V AC 3PH, 575V AC 3PH <sup>†</sup> (*requires stand-alone mounted transformer)	230V AC 3PH, 460V AC 3PH, 575V AC 3PH <sup>†</sup> (*requires stand-alone mounted transformer)
Hinged Guides	Provides easy access for maintenance	N/A	N/A	N/A
Warranty	5-Year Limited	5-Year Limited	5-Year Limited	5-Year Limited
Curtain Color Options Actual colors may vary due to fluctuation in the printing process. Always request a color sample from your Overhead Door™ Distributor for accurate color matching.	<p>Red Blue Orange Gray</p>	<p>Black Blue</p>	<p>Black Blue</p>	<p>Red Blue White Gray</p>

Notes

<sup>2</sup> Wind load is the ultimate pressure tested at door width of 20'.

<sup>2</sup> Wind load is the ultimate pressure tested at door width of 19'.

<sup>1</sup> Automatic reset not available with low headroom model. Updated guide design allows for easy manual reset.

<sup>2</sup> Wind load is the ultimate pressure tested at door width of 19'.

<sup>2</sup> Wind load is the ultimate pressure tested at door width of 10'.

<sup>3</sup> Applications with air curtain may require 460V or 575V.

\* Height and width of door may affect opening speed. Please consult factory for specifics.



Metal Door  
**RAPIDSHIELD® 998**



Full-View  
Metal Door  
**RAPIDVIEW® 999**



Parking garages, Manufacturing,  
Auto Dealerships

Auto Dealerships, Retail,  
Manufacturing

Interior/Exterior  
(Mount Inside)

Interior/Exterior  
(Mount Inside)

26'

20'

21'

21'

Up to 80"/sec

Up to 80"/sec

Up to 20"/sec

Up to 20"/sec

N/A

N/A

N/A

N/A

N/A

N/A

Up to 100.0 psf\*

Up to 50.0 psf

N/A

N/A

N/A

N/A

Dual-walled aluminum

Aluminum and scratch-resistant  
polycarbonate

Optional scratch-resistant  
polycarbonate panels

Scratch-resistant  
polycarbonate panel

Direct drive motor and gearbox system  
with field changeable universal handing  
and door stop safety device

Direct drive motor and gearbox system  
with field changeable universal handing  
and door stop safety device

Variable frequency drive NEMA 4X cULus listed;  
Onboard self diagnostic and service reminder;  
Built-in padlockable fused disconnect

Variable frequency drive NEMA 4X cULus listed;  
Onboard self diagnostic and service reminder;  
Built-in padlockable fused disconnect

Integrated light curtain

Integrated light curtain

Wireless reversing edge

Wireless reversing edge

230V AC 3PH, 460V AC 3PH,  
575V AC 3PH†  
(†requires stand-alone mounted transformer)

230V AC 3PH, 460V AC 3PH,  
575V AC 3PH†  
(†requires stand-alone mounted transformer)

Provides easy access for maintenance


Provides easy access for maintenance

5-Year Limited

5-Year Limited



Silver powder coat made  
to mimic anodized aluminum



Approximately 200 RAL powder coat finishes available.

## RAPIDFLEX® FABRIC & RUBBER DOORS

### MODELS 994/995/995LH/997

Well-suited for applications where forklifts and commercial vehicles can quickly enter from the outside while resisting strong wind and the elements. Ideal for manufacturing facilities or extreme environments.

- Staged head plate design for easy installation
- Heavy-duty strut with roller wind lock on Model 994
- Actively heated Thermoguides™ on Model 997 ensures the complete height of the guide has uniform temperature to prevent condensation
- Powder coated high visibility guides (Standard)
- Model 995LH is specifically designed for applications with low headroom



Model 995LH

## RAPIDSHIELD® / RAPIDVIEW® METAL DOORS

### MODELS 998/999

Deliver security and durability with opening speed of up to 80" per second.

- Model 998 provides a solid aluminum curtain. Ideal for applications where security and privacy are a priority.
- Model 999 is a full-view door with polycarbonate panels for light infiltration and is perfect for high traffic applications requiring aesthetic appeal and visibility.
- Model 998 available with FBC approved HVHZ impact resistance.
- Optional perforated, vision or insulated slats available.

† Wind load is the ultimate pressure tested at door width of 15'.

\* Up to 50.0 psf with optional vision panels.

† Wind load is the ultimate pressure tested at door width of 15'.



Model 999



Tools to help you  
get the job done.

## Architect's Edge

24/7 Self-service options at [overheaddoor.com](https://overheaddoor.com)

- Custom Automated Drawing Generator
- Specs
- CAD Drawings
- BIM Object Library
- Continuing Education
- Architectural Services Contact

### The original, innovative choice for unequalled quality and service.

Overhead Door Corporation pioneered the sectional garage door industry, inventing the first sectional garage door in 1921 and the first electric door operator in 1926. Today, we continue to be the industry leader through the strength of our product innovation, superior craftsmanship and outstanding customer support, underscoring a legacy of quality, expertise and integrity. That's why design and construction professionals specify Overhead Door™ products more often than any other brand. Our family of over 400 Overhead Door™ Distributors across the U.S. and Canada not only share our name and logo, but also our commitment to excellence.



**INDUSTRY EXPERTS,  
DELIVERING TOTAL SOLUTIONS**



2501 S. State Hwy. 121 Bus., Suite 200, Lewisville, TX 75067  
1-800-929-DOOR • [sales@overheaddoor.com](mailto:sales@overheaddoor.com)  
[overheaddoor.com](https://overheaddoor.com)